EL-2645 EL SERIES SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM



STANDARD FEATURES

- ▶ Electric drive
- ▶ Drive at full height indoor & outdoor
- ▶ 110V power-to-platform
- Proportional controls
- > 30A Charger
- Non-slip deck
- ▶ All motion alarm
- Flashing beacon
- ▶ Removable platform controls
- Self-locking gate
- Liftable with forklift or crane

- Dual Maintenance bars
- ▶ Onboard diagnostic system
- Manual decent cable
- Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- Non-marking tires
- ▶ Horn
- ► CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

NSI A92.20

OPTIONS

- ▶ Tool Tray
- ▶ Pipe Rack

PRELIMINARY BROCHURE SUBJECT TO CHANGE



EL SERIES

| | SERIES -PROPELLED MOBILE ELEVATED WORK PLA | ateorm | | |
|-----------------------------------|---|-------------|---------------|--|
| | CIFICATIONS | (II OI (II) | | |
| A | Working Height (3 Person Indoor/1 Person Outdoor) | 32.3ft | 10 m | |
| В | Platform Height Maximum (3 Person Indoor/1 Person Outdoor) | 26.3 ft | 8 m | |
| C | Platform Height Minimum | 47.6 in | 1.21 m | |
| D | Ground Clearance Elevated | 0.79 in | 2 cm | |
| E | Ground Clearance Lowered | 4.7 in | 12 cm | |
| F | Overall Length w/ Step | 97.3 in | 2.47 m | |
| G | Overall Width | 45 in | 1.15 m | |
| н | Stowed Height (Rails Unfolded) | 91 in | 2.31 m | |
| | Stowed Height (Rails Folded) | 65.7 in | 1.67 m | |
| 1 | Platform Length | 91 in | 2.31 m | |
| J | Platform Width | 45 | 1.14 m | |
| K | Slide Out Extension Deck Length | 39.4 in | 1 m | |
| | Wheelbase | 73.2 | 1.86 m | |
| | Tires | 15 x 5 in | 38 x 12.7 cm | |
| PER | FORMANCE | | | |
| Rated Occupancy (Indoor/Outdoor) | | 3/1 Pe | 3/1 Person(s) | |
| Platform Capacity | | 992 lbs | 450 kg | |
| Slide Out Extension Deck Capacity | | 330 lbs | 150 kg | |
| Gradeability | | 2 | 25% | |
| Inside Turn Radius | | 0 in | 0 cm | |
| Drive Speed Elevated | | 0.4 mph | 0.6 km/h | |
| Drive | e Speed Lowered | 2.8 mph | 4.5 km/h | |
| Working Slope | | 2° | 2°/3° | |

| Working Slope | 2°/3° | |
|-------------------------|------------|---------|
| Lift Speed (Up/Down) | 35 s | |
| Weight | 5577.7 lbs | 2530 kg |
| POWER | | |
| Hydraulic Tank Capacity | 7.1 gal | 27 L |
| attery 4 x 6V 315 Ah | | 15 Ah |
| | | |



