

# TH SERIES TELEHANDLERS



**PRELIMINARY BROCHURE**  
SUBJECT TO CHANGE

# TELEHANDLERS

	TH-626	TH-842	TH-944	TH-1044	TH-1056	TH-1256	
<b>DIMENSIONS</b>	Maximum Lift Height	<b>26 ft</b> 7.9 m	<b>42 ft</b> 12.8 m	<b>44 ft</b> 13.4 m	<b>44.8 ft</b> 13.64 m	<b>56 ft</b> 17.07 m	<b>56 ft</b> 17.07 m
	Maximum Forward Reach	<b>11 ft</b> 3.3 m	<b>28.8 ft</b> 8.8 m	<b>30.8 ft</b> 9.4 m	<b>30.8 ft</b> 9.4 m		
	Up and Over Height						
	Stowed Length w/o forks		<b>19.5 ft</b> 5.9 m	<b>20.3 ft</b> 6.2 m	<b>20.3 ft</b> 6.2 m		
	Overall Width		<b>8.1 ft</b> 2.46 m	<b>8.1 ft</b> 2.46 m	<b>8.1 ft</b> 2.46 m	<b>8.4 ft</b> 2.56 m	<b>8.4 ft</b> 2.56 m
	Stowed Height		<b>8.3 ft</b> 2.53 m	<b>8.3 ft</b> 2.53 m	<b>8.3 ft</b> 2.53 m		
	Wheelbase		<b>11.3 ft</b> 3.4 m	<b>11.3 ft</b> 3.4 m	<b>11.3 ft</b> 3.4 m	<b>11.3 ft</b> 3.4 m	<b>11.3 ft</b> 3.4 m
	Inside Tire Width		<b>6.8 ft</b> 2.07 m	<b>6.8 ft</b> 2.07 m	<b>6.8 ft</b> 2.07 m	<b>6.9 ft</b> 2.1 m	<b>6.9 ft</b> 2.1 m
	Ground Clearance		<b>17 in</b> 43 cm	<b>17 in</b> 43 cm	<b>17 in</b> 43 cm		
	Tires	<b>370/75-28</b>	<b>370/75-28</b>	<b>370/75-28</b>	<b>400/75-28</b>	<b>400/75-28</b>	<b>400/75-28</b>
Standard Forks	<b>4 x 2 x 48 in</b> 12 x 5 x 120 cm	<b>4 x 2 x 48 in</b> 12 x 5 x 120 cm	<b>4 x 2 x 48 in</b> 12 x 5 x 120 cm	<b>4 x 2 x 48 in</b> 12 x 5 x 120 cm	<b>4 x 2 x 48 in</b> 12 x 5 x 120 cm	<b>4 x 2 x 48 in</b> 12 x 5 x 120 cm	
<b>SPECIFICATIONS</b>	Maximum Lifting Capacity	<b>6,000 lbs</b> 2,722 kg	<b>8,000 lbs</b> 3,629 kg	<b>9,000 lbs</b> 4,082 kg	<b>10,000 lbs</b> 4,536 kg	<b>10,000 lbs</b> 4,536 kg	<b>12,000 lbs</b> 5,443 kg
	Maximum Lifting Capacity at Full Height	<b>4,409 lbs</b> 2,000 kg	<b>6,000 lbs</b> 2,722 kg	<b>7,000 lbs</b> 3,175 kg	<b>7,000 lbs</b> 3,175 kg		
	Maximum Lifting Capacity at Max Reach	<b>1,984 lbs</b> 900 kg	<b>1,200 lbs</b> 544 kg	<b>1,100 lbs</b> 498 kg	<b>2,700 lbs</b> 1,224 kg		
	Operating Weight		<b>23,920 lbs</b> 10,850 kg	<b>25,624 lbs</b> 11,450 kg	<b>27,117 lbs</b> 12,300 kg	<b>31,559 lbs</b> 14,315 kg	<b>36,600 lbs</b> 16,601 kg
	Inside Turning Radius		<b>57 in</b> 1.44 m	<b>57 in</b> 1.44 m	<b>57 in</b> 1.44 m		
	Outside Turning Radius		<b>146 in</b> 3.7 m	<b>146 in</b> 3.7 m	<b>146 in</b> 3.7 m		
	Drive Speed		<b>20 mph</b> 32 km/h	<b>20 mph</b> 32 km/h	<b>20 mph</b> 32 km/h	<b>19 mph</b> 30 km/h	<b>18 mph</b> 29 km/h
	Frame Leveling (Tilt/Sway)		<b>10°/10°</b>	<b>10°/10°</b>	<b>10°/10°</b>	<b>10°/10°</b>	<b>10°/10°</b>
	Tilt Angle		<b>122°</b>	<b>122°</b>	<b>122°</b>		
	Boom Lifting Angle	<b>70°</b>	<b>69°</b>	<b>69°</b>	<b>69°</b>		
Stabilizer	<b>NO</b>	<b>NO</b>	<b>NO</b>	<b>YES</b>	<b>YES</b>	<b>YES</b>	
<b>POWER</b>	Power Source	<b>Diesel</b>	<b>Diesel</b>	<b>Diesel</b>	<b>Diesel</b>	<b>Diesel</b>	<b>Diesel</b>
	Engine Make and Model	<b>Deutz</b> <b>3.6TCD T4</b>	<b>Deutz</b> <b>3.6TCD T4</b>	<b>Deutz</b> <b>3.6TCD T4</b>	<b>Deutz</b> <b>3.6TCD T4</b>	<b>Deutz</b> <b>3.6TCD T4</b>	<b>Deutz</b> <b>3.6TCD T4</b>
	Standard Horsepower	<b>74 hp</b>	<b>74 hp</b>	<b>74 hp</b>	<b>74 hp</b>	<b>100 hp</b>	<b>120 hp</b>
	Optional Engine Upgrade	-	-	<b>100 hp</b>	<b>100 hp</b>	<b>120 hp</b>	<b>134 hp</b>
	Fuel Tank		<b>40 gal</b> 150 L	<b>40 gal</b> 150 L	<b>40 gal</b> 150 L		
	Hydraulic Tank		<b>40 gal</b> 150 L	<b>40 gal</b> 150 L	<b>40 gal</b> 150 L		

## ADDITIONAL INFORMATION COMING SOON

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Custom Equipment LLC. reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. ©2024 Custom Equipment LLC. All rights reserved.  
1|24 Part No. TH-00007