

VM-26J

VERTICAL MAST SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM



STANDARD FEATURES

- ▶ AC electric drive
- ▶ Proportional controls
- ▶ Silent drive
- ▶ Zero tailswing
- ▶ Tool tray
- ▶ Drive at full height
- ▶ Motion alarm
- ▶ Onboard diagnostic display
- ▶ Load sensing
- ▶ Overload alarm
- ▶ Tilt alarm

- ▶ Automatic battery water filling
- ▶ Non-marking tires
- ▶ Electric brake release
- ▶ Pothole protection
- ▶ Emergency lowering system
- ▶ CAN communication Protocol
- ▶ Crane lift point
- ▶ Hour meter
- ▶ Horn
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20

PRELIMINARY BROCHURE
SUBJECT TO CHANGE

VM-26J

VERTICAL MAST SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

DIMENSIONS

	Working Height	31.6 ft	9.8 m
A	Maximum Platform Height	25.6 ft	7.8 m
	Horizontal Reach	10.3 ft	3.15 m
B	Up and Over Clearance	21 ft	6.4 m
C	Stowed Height	6.5 ft	1.99 m
D	Stowed Length	8.8 ft	2.67 m
E	Chassis Length	5.6 ft	1.7 m
F	Width	3.3 ft	0.99 m
G	Platform Length	42.1 in	1.07 m
H	Platform Width	38.9 in	0.99 m
I	Ground Clearance Elevated	1.6 in	0.04 m
J	Ground Clearance Stowed	3.9 in	0.1 m
K	Wheelbase	47.2 in	1.2 m

SPECIFICATIONS

Occupants (Indoor/Outdoor)		
Platform Capacity	441 lbs	200 kg
Tailswing	0 in	0 m
Drive Speed Stowed	3.7 mph	6 km/h
Drive Speed Elevated	0.4 mph	0.65 km/h
Gradeability	25%	
Jib Rotation	125°	
Turntable Rotation	350°	
Working Slope	2°/3°	
Tires	15.9 x 5 in	41 x 13 cm
Weight	6,173 lbs	2800 kg

POWER

Hydraulic Tank Capacity	
Batteries	24V / 250A

