

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT LLC



HB-1030

SELF-PROPELLED AERIAL WORK PLATFORM

FEATURES & SPECIFICATIONS

HB-1030

LARGE WORK PLATFORM

Includes 30 in (76.2 cm) slideout deck extension for extra supplies and work space, extension is supported mid-rail to eliminate jams.

COUNTER ROTATING WHEELS

Will not cause carpet to buckle, helps protect sensitive floors and prevent surface scuffs on job site.

LOW STOWED HEIGHT

Low entry height allows for easy loading of materials and tools onto the platform.

LOW FLOOR LOADING

Extremely lightweight design allows for use on delicate or sensitive surfaces.

USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear on the job site.

OVERSIZED 1.25 IN (3.18 CM) PINS

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

NON-MARKING WHEELS

Protect sensitive floors and prevent surface scuffs on job site.

NON-SKID DECK

Large durable platform provides safe and ample working area.

BUILT IN TOOL TRAY

Keeps tools and supplies organized and within reach.

DUAL USB PORT

Allows users ability to charge mobile devices directly from platform.



HEIGHTS

	US	METRIC
Working Height	16 ft	4.9 m
Platform Height Max	10 ft	3 m
Platform Height Min	21 in	53.3 cm
Ground Clearance Raised	0.4 in	1 cm
Ground Clearance Lowered	2 in	5.1 cm

MEASUREMENTS

Overall Length	63.5 in	161.3 cm
Overall Width	30 in	76.2 cm
Stowed Height	65.6 in	166.7 cm
Platform Length	60 in	152.4 cm
Platform Width	25 in	63.5 cm
Platform Extension	30 in	76.2 cm

PERFORMANCE

Platform Capacity	750 lb	340.2 kg
Rated Occupancy	2 person	2 person
Extension Capacity	250 lb	113.4 kg
Weight	1273 lb	577.4 kg
Gradeability	25%	25%
Inside Turn Radius	21 in	53.3 cm
Drive Speed Raised	0.7 mph	0.31 m/s
Drive Speed Lowered	2.5 mph	1.12 m/s
Lift Speed Up/Down	15/14 sec	15/14 sec
Power Source	(2) 12V DC	(2) 12V DC
Tires Front/Rear	8/10 in	20.3/25.4 cm

FLOOR LOADING

Min Wheel Load	62.7 psi	432.3 kPa
Max Wheel Load	99.3 psi	684.6 kPa
Min Machine Load	97.2 psf	4.7 kPa
Max Machine Load	153.9 psf	7.4 kPa

1-866-334-0756 // WWW.HYBRIDLIFTS.COM

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Hy-Brid Lifts reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Hy-Brid Lifts™ is a trademark of Custom Equipment, LLC ©2018 Custom Equipment, LLC All rights reserved.
05/16 Part No. L01-04

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT LLC