

FEATURES & SPECIFICATIONS

HB-P4.5

INCREASED WORK SITE SAFETY

Sturdy and easy to operate Hy-Brid Lifts are the safe and efficient alternative to ladders or scaffolding on a job site.

COMPACT DESIGN

The HB-P4.5 is 70 cm wide and can easily maneuver through doors and onto standard personnel elevators.

MAINTENANCE FREE

Maintenance free AGM Battery and easy access panels improve life cycle and cost of ownership.

LOW FLOOR LOADING

Extremely lightweight design makes the lift easy to push around and allows for use on delicate or sensitive surfaces.

USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear on the job site.

OVERSIZED 3.18 CM PINS

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

INTEGRATED HYDRAULIC SYSTEM

Pump and cylinder system are integrated providing less potential leak points.

TOTAL-LOCK REAR CASTERS

Prevents unwanted wheel and caster rotation

AUTO-LOCK BRAKES ON FRONT TIRES

Prevents machine surfing during use.

NON-MARKING WHEELS

Protect sensitive floors and prevent surface scuffs on job site.





HEIGHTS	METRIC	
Working Height	4.5 m	
Platform Height Max	2.5 m	
Platform Height Min	64.1 cm	
Ground Clearance Lowered	4.1 cm	
MEASUREMENTS		
Overall Length	109.2 cm	
Overall Width	70 cm	
Stowed Height	174.1 cm	
Platform Length	94 cm	
Platform Width	55.9 cm	
PERFORMANCE		
Platform Capacity	249.5 kg	
Rated Occupancy	1 person	
Weight	350.6 kg	
Lift Speed Up/Down	16/16 sec	
Power Source	12V DC	
Tires Front/Rear	20.3/ 20.3 cm	
FLOOR LOADING		
Min Wheel Load	1415.5 kPa	
Max Wheel Load	2422.8 kPa	
Min Machine Load	5.5 kPa	· · · · · · · · · · · · · · · · · · ·
Max Machine Load	9.4 kPa	

1-866-334-0756 // WWW.HYBRIDLIFTS.COM