

EL-2632 EL SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM



STANDARD FEATURES

- ▶ Electric drive
- ▶ Drive at full height indoor & outdoor
- ▶ 110V power-to-platform
- ▶ Proportional controls
- ▶ 30A Charger
- ▶ Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- ▶ Self-locking gate
- ▶ Lifiable with forklift or crane
- ▶ Dual Maintenance bars
- ▶ Onboard diagnostic system
- ▶ Manual decent cable
- ▶ Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- ▶ Non-marking tires
- ▶ Horn
- ▶ CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20

OPTIONS

- ▶ Tool Tray
- ▶ Pipe Rack

PRELIMINARY BROCHURE
SUBJECT TO CHANGE

EL-2632

EL SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

SPECIFICATIONS

A	Working Height (2 Person Indoor/1 Person Outdoor)	32.3ft	10 m
B	Platform Height Maximum (2 Person Indoor/1 Person Outdoor)	26.3 ft	8 m
C	Platform Height Minimum	47.6 in	1.21 m
D	Ground Clearance Elevated	0.79 in	2 cm
E	Ground Clearance Lowered	3.5 in	9 cm
F	Overall Length w/ Step	97.3 in	2.47 m
G	Width	31.5 in	0.8 m
H	Stowed Height (Rails Unfolded)	91 in	2.31 m
	Stowed Height (Rails Folded)	71 in	1.8 m
I	Platform Length	91 in	2.32 m
J	Platform Width	33.5 in	0.85 m
K	Slide Out Extension Deck Length	34 in	0.86 m
	Wheelbase	73.2 in	1.86 m
	Tires	15 x 5 in	38 x 12.7 cm

PERFORMANCE

Rated Occupancy (Indoor/Outdoor)	2/1
Platform Capacity	529 lbs 240 kg
Slide Out Extension Deck Capacity	265 lbs 120 kg
Gradeability	25%
Inside Turn Radius	0 in 0 cm
Drive Speed Elevated	0.4 mph 0.6 km/h
Drive Speed Lowered	2.8 mh 4.5 km/h
Working Slope	2°/3°
Lift Speed (Up/Down)	44/38 s
Weight	4486 lbs 2035 kg

POWER

Hydraulic Tank Capacity	6.6 gal 25 L
Battery	4 x 6V 225 Ah

