## EL-2645 EL SERIES SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM



#### **STANDARD FEATURES**

- ▶ Electric drive
- ▶ Drive at full height indoor & outdoor
- ▶ 110V power-to-platform
- Proportional controls
- > 30A Charger
- Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- Self-locking gate
- Liftable with forklift or crane

- ▶ Dual Maintenance bars
- ▶ Onboard diagnostic system
- Manual decent cable
- Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- ▶ Non-marking tires
- **Horn**
- ► CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

#### **STANDARDS COMPLIANCE**

NSI A92.20

### **OPTIONS**

- ▶ Tool Tray
- ▶ Pipe Rack

# PRELIMINARY BROCHURE SUBJECT TO CHANGE



	<b>SERIES</b> :-PROPELLED MOBILE ELEVATED WORK PLATF	E∩PM		
	CIFICATIONS	ONM		
A	Working Height (3 Person Indoor/1 Person Outdoor)	32.3ft	10 m	
В	Platform Height Maximum (3 Person Indoor/1 Person Outdoor)	26.3 ft	8 m	
C	Platform Height Minimum	47.6 in	1.21 m	
D	Ground Clearance Elevated	0.79 in	2 cm	
E	Ground Clearance Lowered	4.7 in	12 cm	
F	Overall Length w/ Step	97.3 in	2.47 m	
G	Overall Width	45 in	1.15 m	
Н	Stowed Height (Rails Unfolded)	91 in	2.31 m	
	Stowed Height (Rails Folded)	65.7 in	1.67 m	
-1	Platform Length	91 in	2.31 m	
J	Platform Width	45	1.14 m	
K	Slide Out Extension Deck Length	39.4 in	1 m	
	Wheelbase	73.2	1.86 m	
	Tires	15 x 5 in	38 x 12.7 cm	
PER	FORMANCE			
Rated Occupancy (Indoor/Outdoor) 3/1 Person(s)		erson(s)		
Platform Capacity		992 lbs	450 kg	
Slide Out Extension Deck Capacity		330 lbs	150 kg	
Gradeability		2	25%	
Inside Turn Radius		0 in	0 cm	
Drive Speed Elevated		0.4 mph	0.6 km/h	
Drive Speed Lowered		2.8 mph	4.5 km/h	

Working Slope	2°/3	2°/3°	
Lift Speed (Up/Down)	35 s		
Weight	5577.7 lbs	2530 kg	
POWER			
Hydraulic Tank Capacity	7.1 gal	27 L	
Battery	4 x 6V 3	4 x 6V 315 Ah	



