



HY-BRID LIFTS 
MADE IN THE USA

PA-1030 SCISSOR



PUSH-AROUND

PUSH-AROUND MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- ▶ Tool holder
- ▶ Parts tray
- ▶ Saloon-style entry gate
- ▶ Onboard battery condition indicator
- ▶ Two-handed vertical operation
- ▶ Oversized scissor pins
- ▶ Maintenance-free design
- ▶ Bumpers
- ▶ Forklift pockets
- ▶ Recessed charger outlet
- ▶ Onboard diagnostics
- ▶ Slide out component drawer
- ▶ Auto-lock front casters
- ▶ Lanyard attach point
- ▶ Horn
- ▶ Manual descent pull cable
- ▶ Tilt alarm
- ▶ Non-slip deck
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20
- ▶ CSA B354.6:17
- ▶ EN 280-1:2022

OPTIONS

- ▶ 110V power-to-platform
- ▶ Flashing beacon
- ▶ AGM batteries
- ▶ Inverter

PA-1030

SCISSOR

SPECIFICATIONS			
A	Working Height (1 Person Indoor)	16 ft	4.9 m
B	Platform Height Maximum (1 Person Indoor)	10 ft	3 m
C	Platform Height Minimum	25.2 in	64 cm
D	Ground Clearance	2.6 in	6.6 cm
E	Overall Length w/ Step	51.3 in	130.3 cm
F	Width	29.8 in	75.7 cm
G	Stowed Height	68.7 in	174.5 cm
H	Platform Length	40.9 in	103.9 cm
I	Platform Width	20.5 in	52.1 cm
Tires (Front/Rear)		8/8 in	20.3 x 20.3 cm

PERFORMANCE			
Rated Occupancy (Indoor/Outdoor)		1 Person	
Platform Capacity		530 lbs	240.4 kg
Inside Turn Radius		Zero	
Lift Speed (Up/Down)		18/ 20 s	
Weight		893 lbs	405.1 kg
Wheel Load at Minimum Capacity		315 psi	2171.9 kPa
Wheel Load at 500 lbs Capacity		369.6 psi	2548.3 kPa
Wheel Load at Maximum Capacity		372.1 psi	2565.5 kPa
POWER			
Hydraulic Tank Capacity		0.8 gal	2.8 L
Battery		1 x 12V Group 27	

