



**HY-BRID LIFTS™**

**PA-1030**  
SCISSOR



## **PUSH-AROUND**

**PUSH-AROUND MOBILE ELEVATED WORK PLATFORM**

### **STANDARD FEATURES**

- ▶ Tool holder
- ▶ Parts tray
- ▶ Saloon-style entry gate
- ▶ Onboard battery condition indicator
- ▶ Two-handed vertical operation
- ▶ Oversized scissor pins
- ▶ Maintenance-free design
- ▶ Bumpers
- ▶ Forklift pockets
- ▶ Recessed charger outlet
- ▶ Onboard diagnostics
- ▶ Slide out component drawer
- ▶ Auto-lock front casters
- ▶ Lanyard attach point
- ▶ Horn
- ▶ Manual descent pull cable
- ▶ Tilt alarm
- ▶ Non-slip deck
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

### **STANDARDS COMPLIANCE**

- ▶ ANSI A92.20
- ▶ CSA B354.6:17
- ▶ EN 280-1:2022

### **OPTIONS**

- ▶ 110V power-to-platform
- ▶ Flashing beacon
- ▶ AGM batteries
- ▶ Inverter

# PA-1030

## SCISSOR

### SPECIFICATIONS

<b>A</b>	Working Height (1 Person Indoor)	<b>16 ft</b>	4.9 m
<b>B</b>	Platform Height Maximum (1 Person Indoor)	<b>10 ft</b>	3 m
<b>C</b>	Platform Height Minimum	<b>25.2 in</b>	64 cm
<b>D</b>	Ground Clearance	<b>2.6 in</b>	6.6 cm
<b>E</b>	Overall Length w/ Step	<b>51.3 in</b>	130.3 cm
<b>F</b>	Width	<b>29.8 in</b>	75.7 cm
<b>G</b>	Stowed Height	<b>68.7 in</b>	174.5 cm
<b>H</b>	Platform Length	<b>40.9 in</b>	103.9 cm
<b>I</b>	Platform Width	<b>20.5 in</b>	52.1 cm
	Tires (Front/Rear)	<b>8/8 in</b>	20.3 x 20.3 cm

### PERFORMANCE

Rated Occupancy (Indoor/Outdoor)	<b>1 Person</b>	
Platform Capacity	<b>530 lbs</b>	240.4 kg
Inside Turn Radius	<b>Zero</b>	
Lift Speed (Up/Down)	<b>18/ 20 s</b>	
Weight	<b>893 lbs</b>	405.1 kg
Wheel Load at Minimum Capacity	<b>315 psi</b>	2171.9 kPa
Wheel Load at 500 lbs Capacity	<b>369.6 psi</b>	2548.3 kPa
Wheel Load at Maximum Capacity	<b>372.1 psi</b>	2565.5 kPa

### POWER

Hydraulic Tank Capacity	<b>0.8 gal</b>	2.8 L
Battery	<b>1 x 12V Group 27</b>	

