

TH SERIES TELEHANDLERS



PRELIMINARY BROCHURE
SUBJECT TO CHANGE

TELEHANDLERS

		TH-842	TH-944	TH-1044	TH-1056	TH-1256
DIMENSIONS	Maximum Lift Height	42 ft 12.80 m	44 ft 13.42 m	44 ft 9 in 13.64 m	56 ft 17.07 m	56 ft 17.07 m
	Maximum Forward Reach	28 ft 9 in 8.76 m	30 ft 10 in 9.42 m	30 ft 10 in 9.42 m		
	Stowed Length w/o forks	234 in 5.96 m	243 in 6.17 m	243 in 6.17 m		
	Overall Width	97 in 2.47 m	97 in 2.47 m	97 in 2.47 m	100.8 in 2.56 m	100.8 in 2.56 m
	Stowed Height	100 in 2.55 m	100 in 2.55 m	100 in 2.55 m		
	Wheelbase	136 in 3.45 m	136 in 3.45 m	136 in 3.45 m	136 in 3.45 m	136 in 3.45 m
	Ground Clearance	17 in 43 cm	17 in 43 cm	17 in 43 cm		
	Tires	14 x 24	14 x 24	14 x 24	14 x 28	14 x 28
	Standard Forks	4 x 2 x 48 in 12 x 5 x 120 cm	4 x 2 x 48 in 12 x 5 x 120 cm	4 x 2 x 48 in 12 x 5 x 120 cm	4 x 2 x 48 in 12 x 5 x 120 cm	4 x 2 x 48 in 12 x 5 x 120 cm
SPECIFICATIONS	Maximum Lifting Capacity	8,000 lbs 3,629 kg	9,000 lbs 4,082 kg	10,000 lbs 4,536 kg	10,000 lbs 4,536 kg	12,000 lbs 5,443 kg
	Maximum Lifting Capacity at Full Height	6,000 lbs 2,722 kg	7,000 lbs 3,175 kg	7,000 lbs 3,175 kg		
	Maximum Lifting Capacity at Max Reach	1,200 lbs 544 kg	1,100 lbs 498 kg	2,700 lbs 1,224 kg		
	Operating Weight	23,920 lbs 10,850 kg	25,624 lbs 11,450 kg	27,117 lbs 12,300 kg	31,559 lbs 14,315 kg	36,600 lbs 16,601 kg
	Inside Turning Radius	57 in 1.45 m	57 in 1.45 m	57 in 1.45 m		
	Outside Turning Radius	146 in 3.7 m	146 in 3.7 m	146 in 3.7 m		
	Drive Speed	20 mph 32 km/h	20 mph 32 km/h	20 mph 32 km/h	19 mph 30 km/h	18 mph 29 km/h
	Frame Leveling (Tilt/Sway)	10°/10°	10°/10°	10°/10°	10°/10°	10°/10°
	Tilt Angle	122°	122°	122°		
	Boom Lifting Angle	69°	69°	69°		
POWER	Stabilizer	No	No	Yes	Yes	Yes
	Power Source	Diesel	Diesel	Diesel	Diesel	Diesel
	Engine Make and Model	Deutz 3.6TCD T4	Deutz 3.6TCD T4	Deutz 3.6TCD T4	Deutz 3.6TCD T4	Deutz 3.6TCD T4
	Standard Horsepower	74 hp	74 hp	74 hp	100 hp	120 hp
	Optional Engine Upgrade	-	100 hp	100 hp	120 hp	134 hp
	Fuel Tank	40 gal 150 L	40 gal 150 L	40 gal 150 L		
	Hydraulic Tank	40 gal 150 L	40 gal 150 L	40 gal 150 L		

ADDITIONAL INFORMATION COMING SOON