

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT LLC



HB-1230

SELF-PROPELLED AERIAL WORK PLATFORM

FEATURES & SPECIFICATIONS

HB-1230

ZERO TURN RADIUS

Maneuver quickly and easily through congested work sites, through doorways and around tight corners.

PROPORTIONAL LIFT AND DRIVE

User friendly joystick control offers smooth lift and speed control.

LARGE WORK PLATFORM

Includes 30 in (76.2 cm) slide out deck extension for extra supplies and manpower, extension is supported mid-rail to eliminate jams.

MAINTENANCE FREE

Maintenance free AGM Batteries and easy access panels improve life cycle and cost of ownership.

LOW FLOOR LOADING

Lightweight design makes the lift easy to maneuver and allows for use on delicate or sensitive surfaces.

USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear on the job site.

OVERSIZED 1.25 IN (3.18 CM) PINS

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

NON-MARKING WHEELS

Protect sensitive floors and prevent surface scuffs on job site.

BUILT IN TOOL TRAY

Keeps tools and supplies organized and within reach.

DUAL USB PORT

Allows users ability to charge mobile devices directly from platform.



HEIGHTS	US	METRIC
Working Height	18 ft	5.5 m
Platform Height Max	12 ft	3.7 m
Platform Height Min	20 in	50.8 cm
Ground Clearance Raised	0.5 in	1.3 cm
Ground Clearance Lowered	2.9 in	7.4 cm
MEASUREMENTS		
Overall Length	56 in	142.2 cm
Overall Width	30 in	76.2 cm
Stowed Height	64 in	162.6 cm
Platform Length	53 in	134.6 cm
Platform Width	25 in	63.5 cm
Platform Extension	30 in	76.2 cm
PERFORMANCE		
Platform Capacity	550 lb	249.5 kg
Rated Occupancy	2 person	2 person
Extension Capacity	250 lb	113.4 kg
Weight	1610 lb	730.3 kg
Gradeability	25%	25%
Inside Turn Radius	Zero	Zero
Drive Speed Raised	0.8 mph	0.36 m/s
Drive Speed Lowered	2.2 mph	0.98 m/s
Lift Speed Up/Down	18/16 sec	18/16 sec
Power Source	(2) 12V DC	(2) 12V DC
Tires Front/Rear	8/12 in	20.3/30.5 cm
FLOOR LOADING		
Min Wheel Load	102.7 psi	707.8 kPa
Max Wheel Load	137.7 psi	949.6 kPa
Min Machine Load	138 psf	6.6 kPa
Max Machine Load	185 psf	8.9 kPa

1-866-334-0756 // WWW.HYBRIDLIFTS.COM

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Hy-Brid Lifts reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Hy-Brid Lifts™ is a trademark of Custom Equipment, LLC ©2018 Custom Equipment, LLC All rights reserved.
05/16 Part No. L01-15

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT LLC