Pre-start Inspection (Self-Propelled Models)



THIS CHECKLIST MUST BE USED AT THE BEGINNING OF EACH SHIFT OR AFTER EVERY SIX TO EIGHT HOURS OF USE. FAILURE TO DO SO COULD AFFECT THE SAFETY OF THE OPERATOR.

Model: Serial Number:				
 Keep inspection records up-to-date. Record and report all discrepancies to your supervisor. A dirty machine cannot be properly inspected. 				
Y-Yes/Acceptable N-No/Unacceptable R-Repaired N/A - Not equipped with this feature	Υ	N	R	N/A
VISUAL INSPECTIONS				
There are no loose or missing parts.				
Check that warning and instructional labels are legible and secure. Ensure that load capacity is clearly ma	rked.			
Check the platform rails and safety gate for damage.				
Platform and base controls are not missing, damaged, or disconnected.				
Electrical cables and wires are not torn, frayed, or disconnected.				
Hydraulic hoses are not torn or loose, and there are no leaks. Hoses and the cables have no worn areas chafing.	or \Box			
Check the tires for damage. Check that wheel axle retaining rings and any set screw(s) in rear wheel are t	tight.			
Check that all snap rings are secure in grooves on pivot pins.				
FUNCTIONAL TESTS				
Gate closes automatically and latches.				
Platform Controls: Check all switches and push buttons for proper operation.				
Emergency Stop (Stops all movement)				
For Actuator-Steered models: Enable Switch (Does not elevate unless enable is pressed)				
For Counter-Rotate Steering models: Drive & Up/Down Mode Switch (Selects drive/steer or elevate m	node)			
Joystick (Return to neutral, drives forward & reverse,) Enable Trigger (Must be activated for joystick-operated movement) For Actuator-Steered models: Thumb rocker steers right & left For Counter-Rotate Steering models: Elevates & lowers				
If so equipped, horn sounds when button is pressed.				
Base Controls: Check all switches and push buttons for proper operation.				
Emergency Stop (Stops all movement)				
For Actuator-Steered models: Key Switch (On or Off) For Counter-Rotate Steering models: Key Switch (Selects Platform Control, Ground Control, or Off)				
Up/Down Rocker Switch (Elevates, Lowers)				
Descent Alarm (Not damaged, sounds for descent; may also sound for drive & elevate, if so equipped)				
Tilt Alarm (Not damaged, sounds when tilted and machine elevated above designated height) If so equipped, elevating beyond this height may also be prevented.				
Master Power Switch disconnects battery				
Wheels: Front and rear wheels rotate freely. For Counter-Rotate Steering models: Front wheels pivot freely.				
Drives in slow speed when elevated.				
Brakes: Machine stops when joystick released.				
Pothole guards deploy and lock when platform is elevated.				
Lift does not elevate when pothole guards are blocked.				

Date:______Inspected by:_____