3.2 | PRE-DELIVERY/ANNUAL/FREQUENT INSPECTION CHECKLIST

Model:

Serial No. _

- Check each item listed below.
- Use proper operating, service, and maintenance manual for specific information and settings
- If an item is found to be unacceptable make the necessary repairs and check the "repaired" box.
- When all items are "acceptable", the unit is ready for service.
- If an item is found to be unacceptable, make the necessary repairs and check the "repaired" box. When all items are "acceptable," the unit is ready for service.



WORK PLATFORMS SHALL BE INSPECTED, SERVICED, AND ADJUSTED TO MANUFACTURER'S REQUIREMENTS BY A QUALIFIED MECHANIC PRIOR TO EACH SALE, LEASE, OR RENTAL, AND EVERY 3 MONTHS OR 150 HOURS, WHICHEVER COMES FIRST, AND ANNUALLY.

Y-Yes/Acceptable N-No/Unacceptable R-Repaired N/A-Not Applicable	Y	Ν	R	N/A					
BASE:									
Inspect slide tracks for damage									
All frame bolts tight									
Pump secure									
DC motors secure									
Batteries fully charged									
Tie rods secure									
WHEELS:									
Snap rings secure									
Bolts/nuts tight									
SCISSORS:									
No broken welds									
No bent beam members									
All rollers turn freely									
Retaining rings secure on pivots									
Maintenance locks: Stored and securely connected									
Scissor beam tube bolts tight									
PLATFORM:									
No bent rails									
No broken welds									
All rails in place/secure									
110V outlet safe/working									
Entrance gate closes freely									

HY-BRID LIFTS

SECTION 3 MAINTENANCE CHECKLISTS

Y-Yes/Acceptable N-No/L	Jnacceptable R -Repaired N/A -Not Applicable	Y	N	R	N/A				
DECALS:									
Legibile									
Correct capacity noted									
Proper placement & quar	ntity.								
RAILS/EXTENDING PLATFORM:									
Extends freely									
Cables in place/secure									
Locks in stowed position									
Locks in extended positio	n								
FUNCTIONS:									
Elevate/Lower operationa	al (see Pre-Start Inspection for details)								
Emergency stop breaks c	ircuits								
BRAKES:									
Operational									
EMERGENCY DOWN:									
Operational									
WIRING:									
Switches secure									
Contactor(s) secure									
Tight on terminals (No lo	ose wiring)								
OTHER:									
Check all hoses for leaks									
Check all fittings for leaks									
Battery charger secure/or	perational								
When tilted past the allowable degree, unit will not elevate									
Warning horn									
Hour meter operational									
Battery indication operational									
Operator's Manual is on the unit									
Overload light & alarm sounds when overloaded (only required for annual inspection on CE Lifts)									
DATE:	INSPECTED BY:								