

ZT SERIES PRE-DELIVERY/ANNUAL/FREQUENT INSPECTION CHECKLIST

Model: _____

Serial No. _____

- Check each item listed below.
- Use proper operating, service, and maintenance manual for specific information and settings
- If an item is found to be unacceptable make the necessary repairs and check the "repaired" box.
- When all items are "acceptable", the unit is ready for service.
- If an item is found to be unacceptable, make the necessary repairs and check the "repaired" box. When all items are "acceptable," the unit is ready for service.



FEATUREWORK PLATFORMS SHALL BE INSPECTED, SERVICED, AND ADJUSTED TO MANUFACTURER'S REQUIREMENTS BY A QUALIFIED MECHANIC PRIOR TO EACH SALE, LEASE, OR RENTAL, AND EVERY 3 MONTHS OR 150 HOURS, WHICHEVER COMES FIRST, AND ANNUALLY.

Y-Yes/Acceptable N-No/Unacceptable R-Repaired N/A-Not Applicable	Y	N	R	N/A
BASE:				
Inspect slide tracks for damage				
All frame bolts tight				
Pump secure				
DC motors secure				
Batteries fully charged				
WHEELS:				
Snap rings secure				
Bolts/nuts tight				
All shields/guards in place				
SCISSORS:				
No broken welds				
No bent beam members				
All rollers turn freely				
Ret. rings secure on pivots				
Maintenance locks: Stored in designated location				
PLATFORM:				
No bent rails				
No broken welds				
All rails in place/secure				
110V outlet safe/working				
Entrance gate closes freely				

ZT SERIES PRE-DELIVERY/ANNUAL/FREQUENT INSPECTION CHECKLIST

Y-Yes/Acceptable N-No/Unacceptable R-Repaired N/A-Not Applicable	Y	N	R	N/A
DECALS:				
Legibile				
Correct capacity noted				
Proper placement & quantity.				
RAILS/EXTENDING PLATFORM:				
Extends freely				
Cables in place/secure				
Locks in stowed position				
Locks in extended position				
FUNCTIONS:				
All functions (Drive,Elevate,Steer) operational (see Pre-Start Inspection for details)				
Pothole guards deploy when platform elevated				
Emergency stop breaks circuits				
Slow speed limit switch set properly				
Pothole interlock functions correctly				
BRKAES:				
Operational				
EMERGENCY DOWN:				
Operational				
WIRING:				
Switches secure				
Contacto(r)s secure				
Tight on terminals (No loose wiring)				
OIL:				
Level 1" from top (when platform stowed)				
OTHER:				
Check all hose for leaks				
Check all fittings for leaks				
Battery charger secure/operational				
Tilt sensor				
Warning horn				
Hour meter operational				
Battery indication operational				
Operator's Manual is on the unit				
Overload light & alarm sounds when overloaded (only required for annual inspection)				
DATE:	INSPECTED BY:			